



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2000140638 A**(43) Date of publication of application: **23.05.00**

(51) Int. Cl. **B01J 23/58**  
**B01D 53/94**  
**B01J 20/08**  
**B01J 21/16**  
**B01J 23/46**  
**B01J 23/63**  
**B01J 23/652**  
**B01J 33/00**

(21) Application number: **10357871**  
 (22) Date of filing: **16.12.98**  
 (30) Priority: **02.09.98 JP 10248459**

(71) Applicant: **TOYOTA MOTOR CORP TOYOTA  
CENTRAL RES & DEV LAB INC**

(72) Inventor: **HACHISUGA ICHIRO  
IKEDA YASUO  
SOFUE YUICHI  
TANAKA TOSHIYUKI  
ANDOU CHIWA  
TAKAHASHI NAOKI**

**(54) CATALYST FOR PURIFYING EXHAUST GAS****(57) Abstract:**

**PROBLEM TO BE SOLVED:** To further improve NOx reducibility of a catalyst contg. a multiple oxide of MgO.Al<sub>2</sub>O<sub>3</sub> or the like as a carrier and to maintain stable NOx purifying property of the catalyst even after it is used at high temp.

**SOLUTION:** This catalyst contains both of a catalyst A, in which a NOx occluding material element is deposited on a carrier contg. a multiple oxide expressed by MO.nAl<sub>2</sub>O<sub>3</sub>, and a catalyst B, in which

a novel metal is deposited on a carrier contg. a refractory other than MO.Al<sub>2</sub>O<sub>3</sub>. Reduction of a specific surface area or reduction of NOx occluding property of the first carrier can be prevented by effect of the catalyst A even if it is used at a high temp. region, and high NOx reducibility is maintained by effect of the catalyst B even if it is used at a high temp. region. Therefore durability of NOx purifying property is improved by coexisting both of the catalyst.

COPYRIGHT: (C)2000,JPO